

Datasheet Databox

Cold aisle containment – manually operated sliding doors

Key technical data

Design	Cold/hot aisle containment for rack rows based on Z-SERVER, SZB IT or DSR IT
Aisle width	1,200 mm
Rack heights / depths	42, 45, 47 U; 1,000 / 1,200 mm; 52 U as a special solution
Doors	Sliding glass doors of aluminium profiles and safety glass, manual or motorised
Options	Roof modules, raised roof, rear wall, add-on cabinets 2 × 150 mm, roof cable routing, aisle lighting

Standard sizes

Rack height	Version	Depth [mm]	RAL 7035	RAL 9005
42 U	without feet	1000	W-8390-64-01-011	W-8390-64-01-161
42 U	without feet	1200	W-8390-64-03-011	W-8390-64-03-161
45 U	without feet	1000	W-8390-64-05-011	W-8390-64-05-161
45 U	without feet	1200	W-8390-64-07-011	W-8390-64-07-161
47 U	without feet	1000	W-8390-64-09-011	W-8390-64-09-161
47 U	without feet	1200	W-8390-64-11-011	W-8390-64-11-161
42 U	with feet	1000	W-8390-64-02-011	W-8390-64-02-161
42 U	with feet	1200	W-8390-64-04-011	W-8390-64-04-161
45 U	with feet	1000	W-8390-64-06-011	W-8390-64-06-161
45 U	with feet	1200	W-8390-64-08-011	W-8390-64-08-161
47 U	with feet	1000	W-8390-64-10-011	W-8390-64-10-161
47 U	with feet	1200	W-8390-64-12-011	W-8390-64-12-161

Source: IT solutions catalogue p. 22–29

Version 10/2026 · Subject to technical changes. All values as per the ZPAS catalogue.

ZPAS GROUP GmbH · Torgauer Straße 231-233 · 04347 Leipzig, Germany · +49 177 2479368 · info@zpasgroup.de · zpas.de