

Datasheet SZB IT

19" network and server rack, 18–47 U

Key technical data

Design	19" floor-standing rack for networks and servers, fully dismountable frame
Load capacity (static)	1,000 kg (depth 600/800 mm; depth 1,000/1,200 mm up to 24 U), 1,500 kg (depth 1,000/1,200 mm from 33 U); on castors type 150: 150 kg, type 300: 500 kg – profile rails 50–150 mm from front and rear, load evenly distributed
Doors	Glass, vision, solid or perforated doors (80 % air permeability); opening angle up to 270°
Colour	RAL 7035 / RAL 9005

Standard sizes

Height	Frame height	Width × depth (mm)
18 U	896 mm	600/800 × 600/800
24 U	1,163 mm	600/800 × 600/800/1000
33 U	1,563 mm	600/800 × 600/800
42 U	1,963 mm	600/800 × 600/800/1000/1200
45 U	2,096 mm	600/800 × 600/800/1000/1200
47 U	2,186 mm	600/800 × 1000/1200

Source: IT solutions catalogue p. 36

Version 10/2026 · Subject to technical changes. All values as per the ZPAS catalogue.

ZPAS GROUP GmbH · Torgauer Straße 231-233 · 04347 Leipzig, Germany · +49 177 2479368 · info@zpasgroup.de · zpas.de