

Datasheet SZE2

Welded baying enclosure, 26 standard sizes

Key technical data

Design	Welded baying enclosure for outdoor and indoor installations, easy to bay
Material	Sheet steel; mounting plate and mounting rails galvanised
Degree of protection	IP 54 to EN 60529 with side panels; IP 55 with additional sealing of the base plate
Finish	RAL 7035, textured epoxy-polyester powder coating; special finish and stainless steel on request
Load capacity	1,000 kg on the mounting plate, 1,600 kg on the mounting rail frame, 150 kg on the swing frame, 20 kg on the door
Scope of delivery	Frame, front door with double-bit lock, rear panel, mounting plate, sliding base plates, blanking plate(s) for the roof
UL	UL certificate of conformity

Standard sizes

Width (flush / protruding sides)	Depth	Height 2,000 mm	Height 2,200 mm
600 / 650 mm	400 mm	WZ-SZE2-2050-...	—
600 / 650 mm	500 mm	WZ-SZE2-2012-...	WZ-SZE2-2212-...
600 / 650 mm	600 mm	WZ-SZE2-2011-...	WZ-SZE2-2211-...
600 / 650 mm	800 mm	WZ-SZE2-2010-...	WZ-SZE2-2210-...
800 / 850 mm	400 mm	WZ-SZE2-2049-...	—
800 / 850 mm	500 mm	WZ-SZE2-2009-...	WZ-SZE2-2209-...
800 / 850 mm	600 mm	WZ-SZE2-2008-...	WZ-SZE2-2208-...
800 / 850 mm	800 mm	WZ-SZE2-2007-...	WZ-SZE2-2207-...
1,000 / 1,050 mm	500 mm	WZ-SZE2-2006-...	WZ-SZE2-2206-...
1,000 / 1,050 mm	600 mm	WZ-SZE2-2005-...	WZ-SZE2-2205-...
1,000 / 1,050 mm	800 mm	WZ-SZE2-2004-...	WZ-SZE2-2204-...
1,200 / 1,250 mm	500 mm	WZ-SZE2-2003-...	WZ-SZE2-2203-...
1,200 / 1,250 mm	600 mm	WZ-SZE2-2002-...	WZ-SZE2-2202-...
1,200 / 1,250 mm	800 mm	WZ-SZE2-2001-...	WZ-SZE2-2201-...

Catalogue number of the standard version: WZ-SZE2-xxxx-S10A-00-111-00-0-011. Special sizes (e.g. 1,800 mm high) and stainless steel on request.

Source: Enclosure systems catalogue p. 10, 20

Version 10/2026 · Subject to technical changes. All values as per the ZPAS catalogue.

ZPAS GROUP GmbH · Torgauer Straße 231-233 · 04347 Leipzig, Germany · +49 177 2479368 · info@zpasgroup.de · zpas.de