

Datasheet SZE3

Bolted baying enclosure, IP 55, 32 standard sizes

Key technical data

Design	Bolted frame of closed profiles, perforated on two levels in a 25 mm grid; easy baying
Standards	Manufactured to EN 62208; degree of protection IP 55 to EN 60529
Material / finish	Frame galvanised sheet steel; doors, panels, plinth powder-coated RAL 7035; mounting plate, swing frame, mounting rails galvanised
Use	Indoor: automation and electrical engineering
Scope of delivery	Frame, front door with double-bit lock, rear panel, full-height mounting plate, top cover, base plates
UL	UL certificate of conformity

Standard sizes

Width	Depth	Height 2,000 mm	Height 2,200 mm
600 mm	400 mm	WZ-SZE3-2032-...	WZ-SZE3-2216-...
600 mm	500 mm	WZ-SZE3-2031-...	WZ-SZE3-2215-...
600 mm	600 mm	WZ-SZE3-2030-...	WZ-SZE3-2214-...
600 mm	800 mm	WZ-SZE3-2029-...	WZ-SZE3-2213-...
800 mm	400 mm	WZ-SZE3-2028-...	WZ-SZE3-2212-...
800 mm	500 mm	WZ-SZE3-2027-...	WZ-SZE3-2211-...
800 mm	600 mm	WZ-SZE3-2026-...	WZ-SZE3-2210-...
800 mm	800 mm	WZ-SZE3-2025-...	WZ-SZE3-2209-...
1,000 mm	400 mm	WZ-SZE3-2024-...	WZ-SZE3-2208-...
1,000 mm	500 mm	WZ-SZE3-2023-...	WZ-SZE3-2207-...
1,000 mm	600 mm	WZ-SZE3-2022-...	WZ-SZE3-2206-...
1,000 mm	800 mm	WZ-SZE3-2021-...	WZ-SZE3-2205-...
1,200 mm	400 mm	WZ-SZE3-2020-...	WZ-SZE3-2204-...
1,200 mm	500 mm	WZ-SZE3-2019-...	WZ-SZE3-2203-...
1,200 mm	600 mm	WZ-SZE3-2018-...	WZ-SZE3-2202-...
1,200 mm	800 mm	WZ-SZE3-2017-...	WZ-SZE3-2201-...

Catalogue number of the standard version: WZ-SZE3-xxxx-S10A-00-111-00-0-011. Non-standard sizes (e.g. 1,800 mm high) by arrangement.

Source: Enclosure systems catalogue p. 62, 70

Version 10/2026 · Subject to technical changes. All values as per the ZPAS catalogue.

ZPAS GROUP GmbH · Torgauer Straße 231-233 · 04347 Leipzig, Germany · +49 177 2479368 · info@zpasgroup.de · zpas.de